



Electric-hydraulic bucket grab of the HLD type



- This grab is designed for operation on crane bridges and similar lifting equipment
- This grab can be used for handling loose materials such as sand, gravel, coal, coke, wooden chips etc.
- The grab design can be adjusted to the client's requirements

These grabs are designed for work:

- in chemical industry facilities
- in the food industry
- underwater
- in the construction industry
- in the metallurgical industry

Our references include:

Slévárna Kuřim, Precheza Přerov, Lovochemie, ŽDAS a.s., Třinecké železářny, a.s., ...

Grab type	Cubature (m ³)	Weight (kg)	Proportions in mm					
			A	B	C	D	E	F
HLD 600-3	0,6	1260	1905	1925	1510	1645	1185	370
HLD 800-3	0,8	1390	2000	1925	1660	1830	1185	370
HLD 1 000-3	1	2100	2280	2290	1760	1920	1435	370
HLD 1 250-3	1,25	2200	2325	2320	1880	2060	1435	370
HLD 1 600-3	1,6	2800	2590	2620	2005	2200	1595	390
HLD 2 000-3	2	2950	2710	2650	2220	2440	1595	390
HLD 3 200-3	3,2	3350	3005	2795	2570	2850	1790	475
HLD 4 000-3	4	3850	3370	2860	2700	2990	2040	475
HLD 5 000-3	5	4150	3550	2910	2990	3330	2040	475
HLD 6 300-3	6,3	4490	3695	3435	3333	3720	2040	475