



Hydraulic grapples for truck lifting device: HR-P



- Main blade of the grab arms and tips made of HARDOX 500
- The center body of the grab and grips made of DOMEX 700
- Design with 4, 5 or 6 grab arms
- The grabs are fitted with Swedish INDEXATOR rotators
- We recommend for line HR-P-M 4-tonne rotator GV4 (34 kg)
- We recommend for lines HR-P-T and HR-P-L a 6-ton rotator GV6 (45 kg)

Grab type	Proportions in mm										
	A	B	C	D	E	F	G	H	I	J	K
HR-P-170/4-M	1 028	1 195	450	730	662	777	445	207	25	453	186
HR-P-170/5-M	1 028	1 195	450	730	662	777	445	207	25	328	186
HR-P-210/4-L	1 223	1 397	626	968	788	860	425	225	35	453	186
HR-P-210/5-L	1 223	1 397	626	968	788	860	425	225	35	350	186
HR-P-210/6-L	1 223	1 397	626	968	788	860	425	225	35	328	186
HR-P-230/4-L	1 360	1 550	690	985	830	955	460	225	35	465	186
HR-P-230/5-L	1 360	1 550	690	985	830	955	460	225	35	372	166
HR-P-230/6-L	1 360	1 550	690	985	830	955	460	225	35	340	166
HR-P-250/4-L	1 500	1 680	684	977	868	1 068	505	225	35	490	186
HR-P-250/5-L	1 500	1 680	684	977	868	1 068	505	225	35	372	186
HR-P-250/6-L	1 500	1 680	684	977	868	1 068	505	225	35	340	186
HR-P-280/5-T	1 555	1 745	780	1 070	810	1 003	405	255	35	520	186
HR-P-280/6-T	1 555	1 745	780	1 070	810	1 003	405	255	35	433	186
HR-P-350/5-T	1 783	1 954	860	1 095	850	1 118	447	255	35	537	186
HR-P-350/6-T	1 783	1 954	860	1 095	850	1 118	447	255	35	466	186

Grab type	Cubature (dm ³)	Weight Design. 1/2	Number of grips	Lifting capacity (kg)	Force F (kg) (210 bar)
HR-P-170/4-M	170	194/183	4	1 500	709
HR-P-170/5-M	170	220/213	5	1 500	709
HR-P-210/4-L	210	213/205	4	1 500	582
HR-P-210/5-L	210	245/232	5	1 500	582
HR-P-210/6-L	210	280/260	6	1 500	582
HR-P-230/4-L	230	248/228	4	1 500	526
HR-P-230/5-L	230	271/265	5	1 500	526
HR-P-230/6-L	230	293/285	6	1 500	526
HR-P-250/4-L	250	282/270	4	1 500	482
HR-P-250/5-L	250	292/280	5	1 500	482
HR-P-250/6-L	250	303/294	6	1 500	482
HR-P-280/5-T	280	383/364	5	2 000	650
HR-P-280/6-T	280	435/420	6	2 000	650
HR-P-350/5-T	350	420/383	5	2 000	644
HR-P-350/6-T	350	471/445	6	2 000	644